

GCE

Mathematics

Unit 4730: Mechanics 3

Advanced GCE

Mark Scheme for June 2018

OCR (Oxford Cambridge and RSA) is a leading UK awarding body, providing a wide range of qualifications to meet the needs of candidates of all ages and abilities. OCR qualifications include AS/A Levels, Diplomas, GCSEs, Cambridge Nationals, Cambridge Technicals, Functional Skills, Key Skills, Entry Level qualifications, NVQs and vocational qualifications in areas such as IT, business, languages, teaching/training, administration and secretarial skills.

It is also responsible for developing new specifications to meet national requirements and the needs of students and teachers. OCR is a not-for-profit organisation; any surplus made is invested back into the establishment to help towards the development of qualifications and support, which keep pace with the changing needs of today's society.

This mark scheme is published as an aid to teachers and students, to indicate the requirements of the examination. It shows the basis on which marks were awarded by examiners. It does not indicate the details of the discussions which took place at an examiners' meeting before marking commenced.

All examiners are instructed that alternative correct answers and unexpected approaches in candidates' scripts must be given marks that fairly reflect the relevant knowledge and skills demonstrated.

Mark schemes should be read in conjunction with the published question papers and the report on the examination.

© OCR 2018

Annotations and abbreviations

Annotation in scoris	Meaning			
√and x				
BOD	Benefit of doubt			
FT	Follow through			
ISW	Ignore subsequent working			
M0, M1	Method mark awarded 0, 1			
A0, A1	Accuracy mark awarded 0, 1			
B0, B1	Independent mark awarded 0, 1			
SC	Special case			
۸	Omission sign			
MR	Misread			
NGE	Not good enough			
Highlighting				
Other abbreviations in	Meaning			
mark scheme				
E1	Mark for explaining			
U1	Mark for correct units			
G1	Mark for a correct feature on a graph			
M1 dep*	Method mark dependent on a previous mark, indicated by *			
cao	Correct answer only			
oe	Or equivalent			
rot	Rounded or truncated			
soi	Seen or implied			
www	Without wrong working			
CWO	Correct working only			

Subject-specific Marking Instructions for GCE Mathematics Pure strand

A Annotations should be used whenever appropriate during your marking.

The A, M and B annotations must be used on your standardisation scripts for responses that are not awarded either 0 or full marks. It is vital that you annotate standardisation scripts fully to show how the marks have been awarded.

For subsequent marking you must make it clear how you have arrived at the mark you have awarded.

An element of professional judgement is required in the marking of any written paper. Remember that the mark scheme is designed to assist in marking incorrect solutions. Correct solutions leading to correct answers are awarded full marks but work must not be judged on the answer alone, and answers that are given in the question, especially, must be validly obtained; key steps in the working must always be looked at and anything unfamiliar must be investigated thoroughly.

Correct but unfamiliar or unexpected methods are often signalled by a correct result following an *apparently* incorrect method. Such work must be carefully assessed. When a candidate adopts a method which does not correspond to the mark scheme, award marks according to the spirit of the basic scheme; if you are in any doubt whatsoever (especially if several marks or candidates are involved) you should contact your Team Leader.

C The following types of marks are available.

М

A suitable method has been selected and *applied* in a manner which shows that the method is essentially understood. Method marks are not usually lost for numerical errors, algebraic slips or errors in units. However, it is not usually sufficient for a candidate just to indicate an intention of using some method or just to quote a formula; the formula or idea must be applied to the specific problem in hand, eg by substituting the relevant quantities into the formula. In some cases the nature of the errors allowed for the award of an M mark may be specified.

Α

Accuracy mark, awarded for a correct answer or intermediate step correctly obtained. Accuracy marks cannot be given unless the associated Method mark is earned (or implied). Therefore M0 A1 cannot ever be awarded.

В

Mark for a correct result or statement independent of Method marks.

Ε

A given result is to be established or a result has to be explained. This usually requires more working or explanation than the establishment of an unknown result.

Unless otherwise indicated, marks once gained cannot subsequently be lost, eg wrong working following a correct form of answer is ignored. Sometimes this is reinforced in the mark scheme by the abbreviation isw. However, this would not apply to a case where a candidate passes through the correct answer as part of a wrong argument.

- When a part of a question has two or more 'method' steps, the M marks are in principle independent unless the scheme specifically says otherwise; and similarly where there are several B marks allocated. (The notation 'dep *' is used to indicate that a particular mark is dependent on an earlier, asterisked, mark in the scheme.) Of course, in practice it may happen that when a candidate has once gone wrong in a part of a question, the work from there on is worthless so that no more marks can sensibly be given. On the other hand, when two or more steps are successfully run together by the candidate, the earlier marks are implied and full credit must be given.
- The abbreviation ft implies that the A or B mark indicated is allowed for work correctly following on from previously incorrect results. Otherwise, A and B marks are given for correct work only differences in notation are of course permitted. A (accuracy) marks are not given for answers obtained from incorrect working. When A or B marks are awarded for work at an intermediate stage of a solution, there may be various alternatives that are equally acceptable. In such cases, exactly what is acceptable will be detailed in the mark scheme rationale. If this is not the case please consult your Team Leader.

Sometimes the answer to one part of a question is used in a later part of the same question. In this case, A marks will often be 'follow through'. In such cases you must ensure that you refer back to the answer of the previous part question even if this is not shown within the image zone. You may find it easier to mark follow through questions candidate-by-candidate rather than question-by-question.

F Unless units are specifically requested, there is no penalty for wrong or missing units as long as the answer is numerically correct and expressed either in SI or in the units of the question. (e.g. lengths will be assumed to be in metres unless in a particular question all the lengths are in km, when this would be assumed to be the unspecified unit.)

We are usually quite flexible about the accuracy to which the final answer is expressed and we do not penalise over-specification.

When a value is given in the paper

Only accept an answer correct to at least as many significant figures as the given value. This rule should be applied to each case.

When a value is not given in the paper

Accept any answer that agrees with the correct value to 2 s.f.

ft should be used so that only one mark is lost for each distinct accuracy error, except for errors due to premature approximation which should be penalised only once in the examination.

There is no penalty for using a wrong value for *g*. E marks will be lost except when results agree to the accuracy required in the question.

G Rules for replaced work

If a candidate attempts a question more than once, and indicates which attempt he/she wishes to be marked, then examiners should do as the candidate requests.

If there are two or more attempts at a question which have not been crossed out, examiners should mark what appears to be the last (complete) attempt and ignore the others.

NB Follow these maths-specific instructions rather than those in the assessor handbook.

For a *genuine* misreading (of numbers or symbols) which is such that the object and the difficulty of the question remain unaltered, mark according to the scheme but following through from the candidate's data. A penalty is then applied; 1 mark is generally appropriate, though this may differ for some units. This is achieved by withholding one A mark in the question.

Marks designated as cao may be awarded as long as there are no other errors. E marks are lost unless, by chance, the given results are established by equivalent working.

'Fresh starts' will not affect an earlier decision about a misread.

Note that a miscopy of the candidate's own working is not a misread but an accuracy error.

- If a graphical calculator is used, some answers may be obtained with little or no working visible. Allow full marks for correct answers (provided, of course, that there is nothing in the wording of the question specifying that analytical methods are required). Where an answer is wrong but there is some evidence of method, allow appropriate method marks. Wrong answers with no supporting method score zero. If in doubt, consult your Team Leader.
- J If in any case the scheme operates with considerable unfairness consult your Team Leader.

4730 Mark Scheme June 2018

	Answer		Marks	Guidance		
1		$I^2 = 0.45^2 + 0.6^2 - 2 \times 0.45 \times 0.6 \times \cos 30^\circ$	M1	Condone missing 2, + for – for M1	If 0 or 1 scored allow max M1 for triangle of velocities / forces. OR	
		I = 0.308	A1	0.30797	$2 \times .3 - I \cos \alpha = .3 \times 1.5 \cos 30^{\circ}$	
		$\frac{\sin \alpha}{0.45} = \frac{\sin 30^{\circ}}{I}$	M1	Allow M marks if mass missing 1 or 2 times	$I \sin \alpha = .3 \times 1.5 \sin 30^{\circ}$ M1M1	
		0.45 I Angle 133.1°, may be shown on diagram	A1 [4]	Accept 46.9(35)° (or 43.1°) correctly shown	A1A1 for <i>I</i> and α [$I_x = 0.210$; $I_y = 0.225$]	
2	(i)	KE term $\frac{1}{2}m \times (3.5)^2$	B1			
		PE term 0.6mg or mgh	B1 B1			
		EE term $\frac{3mg(h-0.6)^2}{2\times0.6}$	ы			
		$-0.6mg + \frac{1}{2}m \times (3.5)^2 =$			OR $+\frac{1}{2}m \times (3.5)^2 =$	
		$-0.6mg + \frac{1}{2}m \times (3.5)^{2} =$ $-mgh + \frac{3mg(h - 0.6)^{2}}{2 \times 0.6}$	M1	All terms present; allow sign errors	OR $+\frac{1}{2}m \times (3.5)^2 =$ $-mg(h-0.6) + \frac{3mg(h-0.6)^2}{2 \times 0.6}$	
		$h^2 - 1.6h + 0.35 = 0$	A1 [5]	CAO	2 × 0.6	
	(ii)	1.34 (m) or $\frac{1}{10} (8 + \sqrt{29})$ only	B1 [1]	1.3385; must be from correct (ii)	[May see 0.2615]	
	(iii)	No; string would be slack oe	B1 [1]	Or string not spring, or no EE in string	[other root less than 0.6]	

	Answer		Marks	Guidance		
3	(i)	$Ae^{-t} = 0.2a$ $\int Ae^{-t} dt = \int 0.2 dv (+c)$ $-Ae^{-t} = 0.2v + c$ c = -A - 1 $v = 5 + 5A - 5Ae^{-t}$	M1* *M1 A1 M1 A1 [5]	Condone wrong sign and missing A Sep variables and show intent to integrate May see $-5Ae^{-t} = v + d$ Attempt to work out c : dep M1M1 Oe	OR $[-Ae^{-t}]_0^t = [0.2v]_5^v$ A1 M1 Or $d = -5A - 5$	
	(ii)	$12 = 5 + 5A - 5Ae^{-\infty}$ $A = 1.4$ $6 = 5 + 5 \times 1.4 - 5 \times 1.4 \times e^{-t}$ $t = \ln\left(\frac{7}{6}\right) \text{ or } 0.154$ $x = 5t + 7t + 7e^{-t}(+c)$ $x = 5t + 7t + 7e^{-t} - 7$ Distance is 0.850 (m) or $12 \ln\left(\frac{7}{6}\right) - 1$	M1 A1ft M1 A1 M1 A1 A1 [7]	(i) must include e ^{-t} term Ft (i) and (their) A 0.15415 Ft (i) (must contain exponential and (their) A); allow sign slips 0.849808	OR find $A = 1.4$, then $1.4e^{-t} = 0.2v \frac{dv}{dx} \qquad M1$ $\frac{v}{12-v} dv = dx \qquad A1$ $\int_{5}^{6} \frac{-(12-v)+12}{(12-v)} dv = \int_{0}^{x} dx \qquad M1$ $x = [-v - \ln(12-v)]_{5}^{6} \qquad A1$ 0.850 (m) A1	

Answer		Marks	G	Guidance	
4	(i)	Radial = $a\dot{\theta}^2$ Transverse = $a\ddot{\theta}$	B1 B1 [2]	Towards centre In direction of θ increasing If 0, SCB1 for both shown by correct arrows, or both magnitudes correct	Accept $2g \sin \theta$; $\frac{v^2}{a}$; $\frac{(R-mg\sin \theta)}{m}$ Accept $g \cos \theta$; $\frac{dv}{dt}$
	(ii)	$mga \sin \theta = \frac{1}{2}mv^{2}$ $F - mg \sin \theta = \frac{mv^{2}}{a}$ $F - mg \sin \theta = \frac{m}{a}(2ag \sin \theta)$ $F = 3mg \sin \theta$	M1* M1* *M1 A1 [4]	Condone missing g and allow $\sin / \cos \cos \cos \sin \cos $	Dep M1M1
	(iii)	At $E, v = \sqrt{ag}$ Vert: $-\frac{1}{2}a = v\cos 30^{\circ}t - \frac{1}{2}gt^2$ $t = \frac{1}{2g}(\sqrt{3ag} \pm \sqrt{3ag + 4ga})$	B1 M1* A1 *M1	soi Allow sign errors and sin / cos confusion for M1 [May see: $-a = \sqrt{3agt} - gt^2$] Ft their 3 term quadratic; allow sign slip	Or, at E , $v = \sqrt{ag}$ B1 $y = x \tan \theta - \frac{gx^2}{2v^2 \cos^2 \theta}$ M1* With $\theta = \pi/3$ A1
		$t = \frac{1}{2} \sqrt{\frac{a}{g}} (\sqrt{3} + \sqrt{7}) \text{ oe}$ Dist is $\sqrt{ag} \sin 30^{\circ} \times \frac{1}{2} \sqrt{\frac{a}{g}} (\sqrt{3} + \sqrt{7}) + (\frac{\sqrt{3}}{2}a)$ $\frac{1}{4} a(3\sqrt{3} + \sqrt{7}) \text{ oe}$	A1 M1 A1 [7]	Or $t = 2.1889 \sqrt{\frac{a}{g}}$ Allow if $+\frac{\sqrt{3}}{2} a$ missing: dep *M1 Accept 1.96(04759) a ; in terms of a only	Put $y = -\frac{1}{2}a$ *M1 (allow +/-) Attempt to solve with $v = \sqrt{(ag)}$ M1 $x = \frac{a}{4}(\sqrt{3} + \sqrt{7})$ A1 (ignore other root) Answer A1

	Answer M		Marks	G	uidance
5	(i)	$1.3 \sin \alpha = V \cos \alpha$ $\text{Speed} = 0.542 \text{ (m s}^{-1}\text{) or } \frac{13}{24}$	M1 A1 A1 [3]	OR speed para is 1.2 before and v after or Vel perp loc = 0.5 (m s ⁻¹) B1 $\tan \alpha = \frac{5}{12} = \frac{v}{0.5} [\text{so } v = \frac{5}{24}]$ M1 0.541666	Speed = $\frac{0.5}{\cos \alpha}$
		Speed = 0.342 (m/s) or $\frac{1}{24}$	111 [8]		
	(ii)	$a = 0.208(33)$ or $\frac{5}{24}$ seen or used	B1	Or $0.5\tan\alpha$ or $(0.542)\sin\alpha$	a vel of A parallel loc after coll
	$5m \times 1.3 \cos \alpha - 2mb = -5m(0.542) \sin \alpha + 2mM1$ *		1M 1*	LCM; allow their 0.542; allow sign	b = speed of B before to left, $c = $ speed of B
		$5m \times 1.3 \times \frac{12}{13} - 2mb = -5m(0.542) \times \frac{5}{13} + 2m$	€A1	errors; allow sin / cos; errors in mass $b + c = 3.52$ or $\frac{169}{48}$	after to right. May cancel <i>m</i>
		$c + (0.542) \sin \alpha = -\frac{5}{6}(-b - 1.3\cos \alpha)$	M1*	NEL; allow their 0.542; allow sign errors; allow sin//cos	
		$c + (0.542) \sin \alpha = -\frac{5}{6}(-b - 1.3\cos\alpha)$ $c + (0.542) \times \frac{5}{13} = -\frac{5}{6}(-b - 1.3 \times \frac{12}{13})$	A1	$c + \frac{5}{24} = -\frac{5}{6}(-b - 1.2)$	$c - \frac{5}{6}b = \frac{19}{24}$
		Attempt to solve for c	*M1	Dep two previous M1 marks	121
		c = 2.03	A1 [7]	$2.03219 \text{ or } \frac{1073}{528}$	$[b = \frac{131}{88} = 1.4886]$

	Answer Marks		Marks	G	Suidance
6	(i)	$mg - \frac{5mg(x-1)}{1.0} = ma$ $-5g(x-1.2) = \ddot{x}$ SHM [with $\omega = 7$] Dist of com from O is 1.2 (m)	M1* A1 A1 *B1 B1 [5]	Using $F = ma$; allow sign errors, missing g , for M1; x is dist from O to mass Correct re-arrangement; allow a for \ddot{x} Dep M1 and $\ddot{x} = -k(x+c)$	OR, if x is ext of string $mg - \frac{5mgx}{1.0} = ma$ $-5g(x - 0.2) = \ddot{x}$ Might be from eqm position $Then mg - \frac{5mg(x+0.2)}{1.0} = ma$ $-5gx = \ddot{x}$
	(ii)	Amplitude = 0.3 and ω = 7 Slack when $-0.2 = 0.3 \cos 7t$ t = 0.329 $v = -0.3 \times 7 \sin(7 \times 0.329)$	B1 M1 A1	May be seen in (i) or (ii) Allow sign error; allow sin / cos 0.328646 OR $\frac{1}{4} \times \frac{2\pi}{7} + \frac{1}{7} \sin^{-1} \left(\frac{2}{3}\right)$ Consistent with displacement eqn; allow their ω and t	OH may be found by energy $-1.5mg + \frac{5mg \times (0.5)^2}{2} = -mgy \text{ M1A1}$ OH =0.875 (m) A1
		$v = (-)1.57$ Under gravity: $s = \frac{1.57^2}{2g} (= 0.125)$ $OH = 0.875 \text{ (m)}$ $t = \frac{1.57}{g} (= 0.160) \text{ or } \frac{\sqrt{5}}{14}$ Time to reach H = 0.488 (s)	M1 A1 M1 A1 [8]	(-)1.56528; $v^2 = \frac{1}{4}g$; $v = \frac{7\sqrt{5}}{10}$ 0.159719; ft their v 0.488365	Or $\frac{5mg \times (0.5)^2}{2} = mgz$ z = 0.625; $1.5 - 0.625 = 0.875Or from 0.125 = 4.9t^2 ft their OH$

Answer		Marks	Guidance		
7	(i)	Mom about A for AC $2W \frac{l}{2} \cos 75^{\circ} = Tl \cos 30^{\circ}$ $T = W \frac{\cos 75^{\circ}}{\cos 30^{\circ}}$	M1 A1 [2]	Allow sign errors; allow sin / cos	l may be cancelled
	(ii)	Rl sin 45° or $2W \frac{l}{2} \cos 75^\circ$ or $W \frac{l}{2} \cos 45^\circ$ Mom about A for whole system	B1 M1	One correct term seen. Must be 3 moment terms with comps: Allow sin / cos; ang and sign errors for	Or for AB
		Rl sin 45° + 2W $\frac{l}{2}$ cos 75° = W $\frac{l}{2}$ cos 45° $\alpha = 0.134$ or $\frac{1}{2}(2 - \sqrt{3})$	A1 A1 [4]	M1; l cancelled May see αW for R ; l may be cancelled	$\alpha W l \sin 45^{\circ} + W \frac{\cos 75^{\circ}}{\cos 30^{\circ}} l \cos 30^{\circ} = W \frac{l}{2} \cos 45^{\circ} $ $\left(\frac{W \cos 45^{\circ} - 2W \cos 75^{\circ}}{2W \sin 45^{\circ}}\right)$
	(iii)	When $\theta = 90^\circ$, $y = 2l \sin 22.5^\circ$ $y > 0.765l$ or $\sqrt{(2 - \sqrt{2})l}$ Mom about A for eqm position $W \frac{l}{2} \cos 45^\circ = 2W \frac{l}{2} \cos \theta$ $\cos \theta = \frac{1}{2} \cos 45^\circ$; or $\cos \theta = \frac{\sqrt{2}}{4}$	M1 A1 M1 A1 A1	Allow $\sin / \cos \cosh \sin \theta$ 0.765367l For M1 allow $\sin / \cos $ and missing '2' Or $\theta = 69.2952$	Or from cosine rule $Accept \ge R$ may be present for M1
		$y = 2l\cos\left(\frac{1}{2}\theta + 22.5^{\circ}\right)$ $y < 1.08l$	M1 A1 [7]	$y = 2l \cos 57.148^{\circ}$ 1.08495 <i>l</i> SC A1 for $y = 0.765l$ and $y = 1.08l$	Ft their θ Accept \leq

OCR (Oxford Cambridge and RSA Examinations) The Triangle Building **Shaftesbury Road** Cambridge **CB2 8EA**

OCR Customer Contact Centre

Education and Learning

Telephone: 01223 553998 Facsimile: 01223 552627

Email: general.qualifications@ocr.org.uk

www.ocr.org.uk

For staff training purposes and as part of our quality assurance programme your call may be recorded or monitored

Oxford Cambridge and RSA Examinations is a Company Limited by Guarantee Registered in England Registered Office; The Triangle Building, Shaftesbury Road, Cambridge, CB2 8EA Registered Company Number: 3484466 **OCR** is an exempt Charity

OCR (Oxford Cambridge and RSA Examinations) Head office

Telephone: 01223 552552 Facsimile: 01223 552553



